

StormSok

The StormSok is specifically designed for the capture of gross pollutants: sediment, trash, and oil and grease. Ideally suited for municipal storm drain retrofits, the StormSok's unique design allows for unit to be removed for maintenance or cleaned out in place using conventional vacuum suction equipment.



APPLICATION	REGULATORY ISSUE	TARGET POLLUTANTS
Municipal storm drain retrofits	MS4 Permits	Sediment, trash, O&G
Commercial/retail/residential	Stormwater Compliance	Sediment, trash, O&G
Litter prone urban areas	Trash TMDLs	Trash ≥ 4700 microns (0.2")
Scrap metal/solid waste/oil storage/etc	Industrial Multi-Sector General Permit	Gross pollutants, O&G
Pre-treatment BMP for new development	Municipal Stormwater Permits	Sediment, trash, O&G
Construction sediment/erosion	Construction Stormwater Permit	Sediment/erosion control



StormSok (round grates)

Part Number	9792-1	9792-2	9792-3	9792-4
Flange/Grate Size	24" dia	26" dia	28" dia	30" dia
Sack Depth	31"	34"	37"	40"
Filtered Flow Rate	2217 gpm	2217 gpm	2217 gpm	2217 gpm
Bypass Flow Rate	1059 gpm	1059 gpm	1059 gpm	1059 gpm
Debris Capacity	3.5 ft. ³	3.9 ft. ³	5.2 ft. ³	6.2 ft. ³
Min. Depth Under Grate	33"	36"	39"	42"

Part Number	9793-1	9793-2	9793-3	9793-4
Flange/Grate Size	24" dia	26" dia	28" dia	30" dia
Sack Depth	13"	16"	19"	22"
Filtered Flow Rate	984 gpm	984 gpm	984 gpm	984 gpm
Bypass Flow Rate	1059 gpm	1059 gpm	1059 gpm	1059 gpm
Debris Capacity	1.7 ft. ³	2.4 ft. ³	3.3 ft. ³	4.4 ft. ³
Min. Depth Under Grate	15"	18"	21"	24"

StormSok inserts for larger diameters grates may be available-contact Fabco Industries Inc., (631) 393-6024 for more information.



StormSok (square grates)

Part Number	9794-1	9795-1
Flange/Grate Size	24" x 24"	24" x 24"
Sack Depth	31"	31"
Filtered Flow Rate	2217 gpm	984 gpm
Bypass Flow Rate	1059 gpm	1059 gpm
Debris Capacity	3.6 ft. ³	1.2 ft. ³
Min. Depth Under Grate	33"	15"

Larger and smaller square and rectangular StormSok may be available-contact Fabco Industries Inc., (631) 393-6024 for more information.

