



NOTES FOR 10135-4S-500 STORMSOK ASSEMBLY AND 10101-5-000 EXPANSION RING:

1. WEIGHT (EMPTY): 25 LB MAX
2. MATERIAL:
 - A) SUPPORT FLANGE: ALUMINUM ALLOY PLATE, 5000 SERIES
 - B) STORMSOK: WOVEN POLYPROPYLENE GEOTEXTILE
 - C) APPARENT OPENING SIZE (AOS): 30 US SIEVE (600 MICRONS)
 - D) EXPANSION RING: ALUMINUM ALLOY CHANNEL, 6000 SERIES
 - E) HARDWARE: STAINLESS STEEL
3. PERFORMANCE CHARACTERISTICS (TYP):
 - A) DEBRIS CAPACITY: 1.6 CU-FT
 - B) FILTERED FLOW RATE: 1130 GPM (2.5 CFS)
 - C) BYPASS FLOW RATE: 1077 GPM (2.4 CFS)
4. DESIGNED TO FIT HARCO 24" ROUND CASTINGS
5. RECOMMENDED MINIMUM STRUCTURE DEPTH: 2-IN BELOW STORMSOK
6. USE WITH FABCO REPLACEABLE STORMSOK, P/N: 10135-5S-102
7. DEEP (22" LONG) STORMSOK IS AVAILABLE ON REQUEST
8. REPLACEABLE OIL BOOM IS AVAILABLE ON REQUEST

REFERENCE VIEW

<p>PROPRIETARY AND CONFIDENTIAL THIS DOCUMENT IS THE PROPERTY OF FABCO INDUSTRIES AND IS CONVEYED WITH THE EXPRESS CONDITION THAT IT AND THE INFORMATION CONTAINED IN IT ARE NOT TO BE USED, DISCLOSED, OR REPRODUCED IN WHOLE OR IN PART, FOR ANY PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF FABCO INDUSTRIES; AND THAT NO RIGHT IS GRANTED TO DISCLOSE OR SO USE ANY INFORMATION CONTAINED IN SAID DOCUMENT.</p>	UNLESS OTHERWISE SPECIFIED REMOVE ALL BURRS BREAK SHARP EDGES .002 - .020 FILLETS .020 MAX DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	TOLERANCES: DEC .00 ± .01 DEC .000 ± .005 FRACT ± 1/16 ANGLE ± 2°	APPROVAL	DATE		
	PROJECT	MATERIAL	DWN CHKR ENGR UPD	M.S. J.P.		2/19/2019 2/19/2019
	FABCO INDUSTRIES, INC. 24 CENTRAL DRIVE FARMINGDALE, NY 11735 WWW.FABCO-INDUSTRIES.COM			TITLE: STORMSOK DRAINAGE STRUCTURE		
	SIZE	DWG. NO.	REV	SCALE: NONE		
B	10162-24-000	A	SHEET 1 OF 1			